



## MINIMUM [ミニマム] Ra95

徹底的にコンパクトサイズを目指したデザイン。  
低色温度が充実したシリーズです。

本体		Ra95 非調光		Ra95 位相制御調光	
C1000 JR12V- 50Wクラス		消費電力 15w   ¥19,800 (税抜き)	消費電力 16w   ¥20,800 (税抜き)	消費電力 10.5w   ¥18,800 (税抜き)	消費電力 11.2w   ¥19,800 (税抜き)
		16° 24°	16° 24°	19° 30°	19° 30°
		3500K ● XS 613 101H ● XS 613 102H ● XS 613 103H ● XS 613 104H	3000K ● XS 613 105H ● XS 613 107H ● XS 613 106H ● XS 613 108H	3000K ● XS 614 105H ● XS 614 107H ● XS 614 106H ● XS 614 108H	2700K ● XS 613 109H ● XS 613 111H ● XS 613 110H ● XS 613 112H
C600 JDR 75Wクラス		消費電力 10.5w   ¥18,800 (税抜き)	消費電力 11.2w   ¥19,800 (税抜き)	消費電力 10.5w   ¥18,800 (税抜き)	消費電力 11.2w   ¥19,800 (税抜き)
		19° 30°	19° 30°	19° 30°	19° 30°
		3000K ● XS 614 105H ● XS 614 107H ● XS 614 106H ● XS 614 108H	3000K ● XS 614 105HC ● XS 614 107HC ● XS 614 106HC ● XS 614 108HC	2700K ● XS 614 109H ● XS 614 111H ● XS 614 110H ● XS 614 112H	2700K ● XS 614 109HC ● XS 614 111HC ● XS 614 110HC ● XS 614 112HC
		2500K ● XS 614 113H ● XS 614 115H ● XS 614 114H ● XS 614 116H	2500K ● XS 614 113HC ● XS 614 115HC ● XS 614 114HC ● XS 614 116HC		

OPTION


位相制御調光器

LC 211 LC 221 LC 702  
LC 212 LC 222 LC 611  
LC 213 LC 602 LC 613

シーンライトコントローラー

LC 603  
LC 615

詳細は、別冊「OS06」カタログまたは  
Webサイトをご覧ください。弊社営業担当までお問い合わせください。



## ショーケーススポットライト

本体		Ra92 非調光		別売	
S300 JDR 35Wクラス		消費電力 3.7w   ¥11,000 (税抜き)	消費電力 3.7w   ¥11,000 (税抜き)		XA 639 001 ¥5,500 (税抜き)
		15° ナロー	57° 拡散		
		4000K ● XS 619 101H ● XS 619 104H	3500K ● XS 619 102H ● XS 619 105H		
		3000K ● XS 619 103H ● XS 619 106H			

OPTION

延長ケーブル

[0.5m] XA 453 026 ¥800 (税抜き)  
[1m] XA 453 027 ¥1,200 (税抜き)  
[3m] XA 453 028 ¥2,000 (税抜き)



## PROSPECT LIGHTING SYSTEM OPTGEAR LED [オプトギア]

複数のLEDを丁寧にレンズ制御したフレアのない光。  
LEDならではの構造で筒の奥行き寸法を抑えたデザインです。

本体		Ra85 非調光			Ra85 位相制御調光			フード		オプション	
S750 JR12V- 50Wクラス		消費電力 10w   ¥15,800 (税抜き)	消費電力 11w   ¥16,800 (税抜き)	消費電力 10w   ¥15,800 (税抜き)	消費電力 11w   ¥16,800 (税抜き)	消費電力 10w   ¥15,800 (税抜き)	消費電力 11w   ¥16,800 (税抜き)			XA 253 241 XA 253 242 ¥1,800 (税抜き)	
		20° 27° 49°	20° 27° 49°	20° 27° 49°	20° 27° 49°						
		4000K ● XS 256 241 ● XS 256 243 ● XS 256 245 ● XS 256 246	4000K ● XS 256 261 ● XS 256 263 ● XS 256 265	3500K ● XS 256 247 ● XS 256 249 ● XS 256 251 ● XS 256 252	3500K ● XS 256 267 ● XS 256 269 ● XS 256 271						
		3000K ● XS 256 248 ● XS 256 250 ● XS 256 252 ● XS 256 252	3000K ● XS 256 268 ● XS 256 270 ● XS 256 272	2700K ● XS 256 253 ● XS 256 255 ● XS 256 257 ● XS 256 257	2700K ● XS 256 273 ● XS 256 275 ● XS 256 277						
		2700K ● XS 256 254 ● XS 256 256 ● XS 256 258 ● XS 256 258	2700K ● XS 256 274 ● XS 256 276 ● XS 256 278								
		2700K ● XS 256 339 ● XS 256 341 ● XS 256 343 ● XS 256 343	2700K ● XS 256 345 ● XS 256 347 ● XS 256 349								
		2700K ● XS 256 340 ● XS 256 342 ● XS 256 344 ● XS 256 344	2700K ● XS 256 346 ● XS 256 348 ● XS 256 350								

OPTION

位相制御調光器

LC 211 LC 221 LC 702  
LC 212 LC 222 LC 611  
LC 213 LC 602 LC 613

シーンライトコントローラー

LC 603  
LC 615

ディフューザー

XA 253 243  
¥3,200 (税抜き)



## PLUGGED [プラグド] 生鮮用

精肉と鮮魚をおいしく見せる光を追及。  
PLUGGEDシリーズと互換性があります。

本体		非調光		オプション	
C3500 CDM-T 35Wクラス		消費電力 38w   ¥30,800 (税抜き)	消費電力 28w   ¥30,300 (税抜き)		XA 253 235 XA 253 236 ¥2,400 (税抜き)
		14° ナロー 22° ミディアム 30° ワイド 52° 拡散 スプレッド	14° ナロー 22° ミディアム 30° ワイド 52° 拡散 スプレッド		
		生鮮 ● XS 411 201 ● XS 411 203 ● XS 411 205 ● XS 411 207 ● XS 411 209 ● XS 411 202 ● XS 411 204 ● XS 411 206 ● XS 411 208 ● XS 411 210	生鮮 ● XS 411 211 ● XS 411 213 ● XS 411 215 ● XS 411 217 ● XS 411 219 ● XS 411 212 ● XS 411 214 ● XS 411 216 ● XS 411 218 ● XS 411 220		
C2750 CDM-T 35Wクラス		消費電力 22w   ¥23,800 (税抜き)	消費電力 17w   ¥23,300 (税抜き)		XA 253 237 XA 253 238 ¥2,100 (税抜き)
生鮮	14° ナロー 22° ミディアム 31° ワイド 46° 拡散 スプレッド	14° ナロー 22° ミディアム 31° ワイド 46° 拡散 スプレッド			
生鮮 ● XS 412 161 ● XS 412 163 ● XS 412 165 ● XS 412 167 ● XS 412 169 ● XS 412 162 ● XS 412 164 ● XS 412 166 ● XS 412 168 ● XS 412 170	生鮮 ● XS 412 171 ● XS 412 173 ● XS 412 175 ● XS 412 177 ● XS 412 179 ● XS 412 172 ● XS 412 174 ● XS 412 176 ● XS 412 178 ● XS 412 180				